



Technical Data Sheet
**GLAZING
VISION**

Eaves Flushglaze Rooflight

FG-E-TDS-v1.6-29.11.2018

Name: Eaves Flushglaze
Code: 402
Type: Fixed Rooflight

Description:

A fixed glazing system comprising powder coated aluminium extrusion and double glazed units. Designed for installation along building eaves. Can also be installed to span opposing gables or as a short extension to an additional building. Available in either single or multipart format, the latter (bespoke) consisting of multiple glazing sections. Flushglaze rooflights are designed to provide maximum daylight with minimal visible internal structure.

Features:

No visible exterior fixings. Lead (or other material) flashing used to hide structural fixings leaving a sleek external finish. Low profile vertical frames mated to high strength overhead support angles. Cill flashing detail to ensure water runs off. Suite of product support data including; sales drawings, schedule and manufacturing information.

Kerb Dimensions:	Min Height: 400mm	Max Height : 4000mm
	Min Span: 400mm	Max Span: 4000mm
	Min Width: 400mm	Max Width: 1600mm
	Min Wall Offset: 0mm	Max Wall Offset: 100mm
	Min Pitch: 3°	Max Pitch: 50°

Example Glass Specification:	Outer:6mm Clear Toughened
	Spacer:14mm Black Silicone Sealed Argon filled cavity with warm edge spacer
	Inner:9.5mm Clear Soft Low E Heat Strengthened Laminated

Thermal Performance (U-Value):	Overall U-Value = 1.3 W/(m ² K) (Based upon dimensions: 1600 Width x 2000 Span x 2000 Height with above example glass specification)
--------------------------------	--

CAD Drawings:	Drawing Number	Description
	402-ASS-056	Double glazed eaves detail (3 sheets)



Technical Data Sheet
**GLAZING
VISION**

Eaves Flushglaze Rooflight

FG-E-TDS-v1.6-29.11.2018

Standard Colour:	RAL 7015 Slate grey
Rooflight Control:	N/A
Power Supply:	N/A
Drive Mechanism:	N/A
Seals:	Silicone.
Security:	Secured to kerb with structural fixings.
Use for Access:	N/A

Optional Extras:	Remote Control:	N/A	Easy Clean Coating:	Yes
	Solenoid Bolt:	N/A	Dual Colour:	No
	Wall Abutted:	Yes	Special Colour:	Yes
	Thermostat:	N/A	Round:	No
	BMS Integration:	N/A	Downlighter:	No
	Trickle Vents:	Yes (bespoke)	Multi-Part:	Bespoke only
			Multi-Part with Glass Fins:	Bespoke only

GLAZINGVISION

Glazing Vision Ltd
Sawmills Road, Diss IP22 4RG

Technical
01379 658300

Email
technicalsales@glazingvision.co.uk