



GLASS CONFORMS TO IMPACT RESISTANCE AND BREAKAGE CHARACTERISTICS OF BS EN 12600:2002. IGUs FABRICATED TO BS EN 1279 AND SUPPLIED IN ACCORDANCE WITH BS 5516-2:2004.

FINISH SPECIFICATION:

POLYESTER POWDER COATED: MIN 40 MICRONS

STANDARD EXTERNAL COLOUR: **RAL 7015 Slate Grey**

STANDARD INTERNAL COLOUR: **RAL 9010 Pure White**

FIXING SPECIFICATION: **A2 STAINLESS STEEL**

SEALANTS SPECIFICATION: **NEUTRAL CURE TO BS5889**

ALL DIMENSIONS mm UNLESS OTHERWISE STATED.

GLAZING VISION

Sawmills Road
Diss Norfolk IP22 4RG
Tel: +44 (0)1379 658300
Email: sales@glazingvision.co.uk
Website: www.glazingvision.co.uk

IT IS GLAZING VISION'S POLICY TO CONTINUOUSLY DEVELOP AND IMPROVE OUR PRODUCTS. WE THEREFORE RESERVE THE RIGHT TO MODIFY OR CHANGE THE DETAIL DESIGN AT OUR DISCRETION AND WITHOUT PRIOR NOTICE.

THIS DRAWING IS COPYRIGHT AND THE SOLE PROPERTY OF GLAZING VISION LTD. THE DESIGNS / INFORMATION IT CONTAINS ARE PRIVATE AND CONFIDENTIAL. IT MUST NOT BE COPIED, EXHIBITED OR COMMUNICATED TO THIRD PARTIES FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS ISSUED WITHOUT THE WRITTEN PERMISSION OF GLAZING VISION LTD.

REV.	REVISION DESCRIPTION	NAME/DATE
-	Initial release	HL 16/10/18
A	Kerb step height revised from 157mm	JSL 14/11/2018
B	Kerb width increased to 243mm	HL 19/03/19
C	Cable exit hole added	HTT 08.10.19

CHECKED JSL 10.10.19 SCALE NTS

PRODUCT GV Standard 3-Wall Box

DESCRIPTION
Kerb Detail

DRAWING NUMBER 606-ASS-107 SHEET 1 of 1

Kerb shown for left hand exit box - mirror for right hand exit