


**Declaration of Performance  
No. 202-DOP-UK-003 – v1.0**

1. Unique identification code of the product-type:  
**202 – GV Standard PitchVent – Double Glazed (6-16-9.5 Laminated)  
Opening roof-window**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4) of the CPR:  
**202 – GV Standard PitchVent – Double Glazed (6-16-9.5 Laminated)  
Opening roof-window**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**An in-plane opening roof-window for the admission of natural light and ventilation into a domestic or commercial location, with both the unit and the roof inclined at an angle of between 15° and 60° and placed at least 800mm above floor level.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):  
**Glazing Vision Ltd, Saw Mills Road, Diss, Norfolk, IP22 4RG, UK**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
**As point 4**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:  
**System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**EN 14351-1:2006+A2:2016**
8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification	
Resistance to wind load	Test pressure	EN 14351-1:2006 +A2:2016	
	Frame deflection		Class 4 Class C
Resistance to snow load	6-16-9.5 Outer: Toughened Inner: Heat Strengthened Laminated		
	Reaction to fire		NPD
External fire performance	NPD		
Watertightness	Non-shielded (A)		Class 9A
	Shielded (B)		NPD
Impact resistance	NPD		
Load-bearing capacity of safety device	N/A		
Acoustic performance	NPD		
Thermal transmittance (using developed area)	1.5 W/(m <sup>2</sup> .K)		
Radiation properties	Solar factor	0.47	
	Light transmittance	0.70	
Air permeability	Class 4		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of Glazing Vision Ltd by:  
**Jeremy Dunn**  
Technical Director



.....08/02/2021.....  
(place and date of issue)



FM596998 EMS613885

Glazing Vision Ltd, Saw Mills Road, Diss, Norfolk, IP22 4RG  
Registered in England. No. 2987024 VAT No. 637 7241 26  
01379 658300 info@glazingvision.co.uk